SEO Fix Guide

https://abhirachnadental.com/best-filler-treatment-in-new-delhi/
Audit #1035 · 2026-08-25 06:20 · Overall 82/100

Total issues: **29** · High: **5** · Medium: **20** · Low: **4**

High (5)

High | Page speed | Priority 78/100 | Easy (~15m)

Cumulative Layout Shift

Poor: 0.254.

Generic best practice

Cumulative Layout Shift should be under 0.1. Set explicit width/height on images, reserve space for embeds and ads, and avoid late-loading fonts that re-flow text.

Code fix

Before:

```
<img src="photo.jpg">
```

After:

```
<img src="photo.jpg" width="800" height="600" alt="...">
```

High | Spam security | Priority 74/100 | Hard (~120m)

No injected/obfuscated code

Potential hacked/injected-code signals: hidden offsite iframe.

Generic best practice

Potential hacked-site/injected-code signals found. Scan source for obfuscated scripts and hidden iframes, check for unexpected admin users and recently modified files, restore from a clean backup, update CMS/plugins, then request a review in Search Console.

Code fix

Before:

```
<script>eval(atob("...base64..."))</script>
```

After:

```
<!-- remove injected script; patch the vulnerability that allowed it -->
```

High | Technical | Priority 72/100 | Medium (~45m)

Response time acceptable

Fetched in 3544 ms — too slow.

Generic best practice

Server is slow. Investigate: enable a CDN, add page caching, optimise database queries, upgrade hosting. TTFB > 800ms hurts every Core Web Vital.

High Meta Priority 65/100 Easy (~15m)

OpenGraph image present

Missing <meta property="og:image">.

Location

Line **3** · `html > head`

```
     2  <html lang="en">
>    3  <head>
     4   <meta charset="UTF-8" />
```

Generic best practice

Add an Open Graph image so links to this page render as a rich card on social platforms. Use 1200x630 px, JPEG/PNG, under 1MB.

Code fix

Before:

```
<head>
  <!-- no og:image -->
</head>
```

After:

```
<head>
  <meta property="og:image" content="https://yoursite.com/og-image.jpg">
  <meta property="og:image:width" content="1200">
  <meta property="og:image:height" content="630">
</head>
```

High Images Priority 64/100 Easy (~15m)

Images have alt text

1 of 9 images missing alt attribute.

Location

Line **932** · `#okapi-wasb-icon`

```
   931  <a href="https://wa.me/919308056390?text=Hi" id="okapi-wasb-button" target="_blank">
>  932   <img id="okapi-wasb-icon" src="https://abhirachnadental.com/wp-content/plugins/wa-sticky-
button/assets/default.png">
   933  </a>  <script type="application/javascript">
```

Generic best practice

Every <img> needs an alt attribute. Alt text helps screen readers, image search ranking, and shows when the image fails to load. Use alt="" only for purely decorative images.

Code fix

Before:

```
<img src="photo.jpg">
```

After:

```
<img src="photo.jpg" alt="Descriptive text describing the image content">
```

Medium (20)

Medium | Page speed | Priority 73/100 | Medium (~45m)

Largest Contentful Paint

Needs improvement: 3.61s.

Generic best practice

Largest Contentful Paint should load within 2.5s. Optimise the largest above-the-fold element: compress hero images, preload critical assets, and eliminate render-blocking resources.

Code fix

Before:

```
<img src="hero.jpg">
```

After:

```
<link rel="preload" as="image" href="hero.webp">
<img src="hero.webp" fetchpriority="high" width="1200" height="600" alt="...">
```

Medium | Page speed | Priority 64/100 | Medium (~45m)

PageSpeed performance score

Score 64/100 — improve.

Generic best practice

Open Lighthouse in Chrome DevTools or PageSpeed Insights — the report lists specific opportunities ranked by impact.

Medium | Page speed | Priority 64/100 | Medium (~45m)

First Contentful Paint

Needs improvement: 3.16s.

Generic best practice

First Contentful Paint should be under 1.8s. Inline critical CSS, defer non-critical CSS/JS, and use a CDN.

Medium | Images | Priority 63/100 | Easy (~15m)

Images have dimensions

8/9 images have explicit dimensions.

Location

Line **202** · `#logo`

```
   201      <a href="https://abhirachnadental.com/">
>  202      <img src="https://abhirachnadental.com/wp-content/uploads/2024/10/abhirachna-logo-big-01.png"
width="584" height="125" alt="Abhirachna Dental &amp; Aesthetics" id="logo" data-height-percentage="62" />
   203      </a>
```

Generic best practice

Set explicit width/height on every <img> to prevent Cumulative Layout Shift. Browser reserves the box before the image loads.

Code fix

Before:

```
<img src="photo.jpg" alt="...">
```

After:

```
<img src="photo.jpg" width="800" height="600" alt="...">
```

Medium | Content | Priority 62/100 | Medium (~45m)

E-E-A-T: Expertise

Moderate:

Generic best practice

Show expertise: author bio with credentials, citations to reputable sources, in-depth coverage of the topic, technical accuracy.

Medium Content Priority 62/100 Medium (~45m)

E-E-A-T: Trustworthiness

Moderate:

Generic best practice

Add trust signals: clear contact info, privacy policy, terms of service, customer reviews, security badges, real photos of team/location.

Medium Page speed Priority 59/100 Easy (~15m)

Compression enabled

No gzip/brotli content-encoding header.

Generic best practice

Enable gzip or Brotli compression on your server. Typically cuts text payload by 70-80% — easy LCP win.

Medium Images Priority 59/100 Medium (~45m)

Modern image formats

No images use webp/avif.

Generic best practice

Convert images to WebP or AVIF — typically 25-50% smaller than JPEG/PNG with no visible quality loss. Use <picture> for fallback.

Code fix

Before:

```
<img src="photo.jpg">
```

After:

```
<picture>
  <source type="image/avif" srcset="photo.avif">
  <source type="image/webp" srcset="photo.webp">
  <img src="photo.jpg" alt="...">
</picture>
```

Medium Content Priority 58/100 Hard (~120m)

E-E-A-T: Experience

Moderate:

Generic best practice

Demonstrate first-hand experience: original photos, personal anecdotes, before/after results, screenshots from the actual product/service.

Medium Content Priority 58/100 Hard (~120m)

E-E-A-T: Authoritativeness

Moderate:

Generic best practice

Build authoritativeness: links from respected sites in your niche, mentions in industry publications, About page detailing your expertise.

Medium | Ssl security | Priority 54/100 | Easy (~15m)

HSTS header present

Missing strict-transport-security header.

Generic best practice

Add Strict-Transport-Security header so browsers refuse HTTP for your domain after the first visit. Bumps SSL Labs grade to A+.

Code fix

After:

```
Strict-Transport-Security: max-age=31536000; includeSubDomains
```

Medium | Links | Priority 53/100 | Easy (~15m)

External links safe

5 external _blank links missing rel=noopener.

Generic best practice

Add rel="noopener noreferrer" to target="_blank" links. Without noopener, the linked page can manipulate your window object — security + perf risk.

Code fix

Before:

```
<a href="https://other.com" target="_blank">External</a>
```

After:

```
<a href="https://other.com" target="_blank" rel="noopener noreferrer">External</a>
```

Medium | Domain security | Priority 53/100 | Easy (~15m)

SPF record present

No SPF (v=spf1) TXT record found for abhirachnadental.com.

Generic best practice

Publish an SPF record so receivers can verify which servers may send mail for your domain — reduces spoofing and improves deliverability. List only your real senders and end with ~all (soft-fail) or -all (hard-fail).

Code fix

Before:

```
# no SPF TXT record
```

After:

```
example.com.  IN  TXT  "v=spf1 include:_spf.google.com ~all"
```

Medium | Domain security | Priority 53/100 | Easy (~15m)

DMARC record present

No DMARC record found at _dmarc.abhirachnadental.com.

Generic best practice

Publish a DMARC record to tell receivers what to do with mail that fails SPF/DKIM, and where to send reports. Start at p=none to monitor, then tighten to quarantine/reject.

Code fix

Before:

```
# no _dmarc TXT record
```

After:

```
_dmarc.example.com.  IN  TXT  "v=DMARC1; p=quarantine; rua=mailto:dmarc@example.com"
```

Medium Geo Priority 48/100 Medium (~45m)

Content provides clear answers

Moderate (5/10).

Generic best practice

Lead each section with a direct, citable answer to the question users would ask. AI engines (ChatGPT, Perplexity) cite the clearest, most specific sentences.

Medium Geo Priority 48/100 Medium (~45m)

High factual density

Moderate (5/10).

Generic best practice

Add concrete facts — numbers, dates, percentages, named sources. Vague prose doesn't get cited; specific data does.

Medium Geo Priority 48/100 Medium (~45m)

Structured for AI extraction

Moderate (5/10).

Generic best practice

Add bulleted lists, sub-headings, definitions, and TL;DR sections. AI engines prefer clearly structured content for extraction.

Medium Geo Priority 48/100 Medium (~45m)

Cites authoritative sources

Moderate (5/10).

Generic best practice

Cite authoritative external sources (links, references). Pages that cite reputable sources are themselves cited more often.

Medium Headings Priority 45/100 Easy (~15m)

Heading hierarchy

Heading levels skipped 2 times.

Generic best practice

Headings should descend logically: H1 → H2 → H3, no jumps. Skipping levels (H1 → H3) breaks accessibility tools and confuses crawlers.

Code fix

Before:

```
<h1>Page Title</h1>
<h3>Section</h3>  <!-- skipped H2 -->
```

After:

```
<h1>Page Title</h1>
<h2>Section</h2>
<h3>Subsection</h3>
```

Medium | Domain security | Priority 44/100 | Easy (~15m)

Security headers configured

Most security headers are missing: strict-transport-security, content-security-policy, x-content-type-options, x-frame-options, referrer-policy, permissions-policy.

Generic best practice

Add the recommended HTTP security headers at the server/CDN level to harden the site.

Code fix

Before:

```
# missing headers
```

After:

```
# nginx
add_header X-Frame-Options "SAMEORIGIN";
add_header X-Content-Type-Options "nosniff";
add_header Referrer-Policy "strict-origin-when-cross-origin";
add_header Permissions-Policy "geolocation=(), microphone=()";
add_header Strict-Transport-Security "max-age=31536000; includeSubDomains";
```

Low (4)

Low | Images | Priority 44/100 | Easy (~15m)

Below-fold images lazy

Only 1 of 9 images use loading="lazy".

Generic best practice

Add loading="lazy" to images below the fold. Saves bandwidth, speeds up initial page load.

Code fix

Before:

```
<img src="below-fold.jpg">
```

After:

```
<img src="below-fold.jpg" loading="lazy" width="..." height="..." alt="...">
```

Low | Content | Priority 43/100 | Medium (~45m)

Readable prose

Flesch reading ease 47.4 — fairly difficult.

Generic best practice

Simplify your prose. Shorter sentences (15-20 words), smaller words (1-2 syllables), more paragraph breaks. Target 8th-grade reading level for a general audience.

Low | Ssl security | Priority 39/100 | Trivial (~5m)

X-Content-Type-Options

Missing x-content-type-options header.

Generic best practice

Add X-Content-Type-Options: nosniff so browsers honour the Content-Type and don't MIME-sniff for malicious files.

Code fix

After:

```
X-Content-Type-Options: nosniff
```

Low | Ssl security | Priority 32/100 | Medium (~45m)

CSP header present

Missing content-security-policy header.

Generic best practice

Add a Content-Security-Policy header to block XSS by whitelisting allowed script/style sources.

Code fix

After:

```
Content-Security-Policy: default-src 'self'; script-src 'self' 'unsafe-inline'
```